



# CERTIFICATE OF ACCREDITATION

## ANSI-ASQ National Accreditation Board

500 Montgomery Street, Suite 625, Alexandria, VA 22314, 877-344-3044

This is to certify that

**Coating and Converting Technologies**  
**80 East Morris Street**  
**Philadelphia PA 19148**

has been assessed by ANAB  
and meets the requirements of international standard

## ISO/IEC 17025:2005

while demonstrating technical competence in the field of

## TESTING

Refer to the accompanying Scope of Accreditation for information regarding the types of tests to which this accreditation applies.

AT-1176  
Certificate Number

  
ANAB Approval

Certificate Valid: 06/03/2016-06/23/2018  
Version No. 002 Issued: 06/03/2016



This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated January 2009).



# ANSI-ASQ National Accreditation Board

## SCOPE OF ACCREDITATION TO ISO/IEC 17025:2005

### Coating and Converting Technologies

80 East Morris Street Philadelphia, PA 19148

Tim Kelly Phone: 215-271-0610

tim.kelly@ccttapes.com www.ccttapes.com

### TESTING

Valid to: June 23, 2018

Certificate Number: AT-1176

#### I. Mechanical

Items, Materials or Products Tested	Specific Tests or Properties Measured	Specification, Standard Method, or Technique Used	Key Equipment or Technology*
Tape Performance	Elongation / Tensile	ASTM D-3759	TMI Universal Tester
Tape Performance	Loop Tack	PSTC-16 / ASTM D-6195	TMI Universal Tester
Tape Performance	Thickness	ASTM D-3652 / 3652M / PSTC-133	TMI Digital Micrometer
Tape Performance	Peel / Release	ASTM D-3330 / 3330M / PSTC-101; ASTM D-903	IMass SP2000
Tape Performance	Tack	ASTM D-2979	TMI Universal Tester
Tape Performance	Shear	ASTM D-3654 / 3654M (A,B,&C) / PSTC-107 (A,B,&C) / PSTC-17 / ASTM D-4498	ChemInst Shear RT-10 Despatch Oven
Tape Performance	Creep Resistance	GM 3622M, 4.3.1 ; Delphi SD2-324, 3.7	N/A
Tape Performance	Temperature	Delphi SD2-324, 3.3	(38 to 260) °C
Tape Performance	Temperature / Humidity	Delphi SD2-324, 3.4	(-60 to 160) °C (0 to 100) %RH



Items, Materials or Products Tested	Specific Tests or Properties Measured	Specification, Standard Method, or Technique Used	Key Equipment or Technology*
Tape Performance	Objectionable Odor (Delphi)	Delphi SD2-324, 3.5	N/A
Tape Performance	Static Shear (Delphi)	Delphi SD2-324, 4.3.1.2	N/A

**Notes:**

1. \* = as applicable.
2. This scope is formatted as part of a single document including Certificate of Accreditation No. AT-1176

  
 \_\_\_\_\_  
 Vice President

